

	MARITIME TERMINAL PTO. ROSALES		PRO-OPE-RE-049
			REV. 04
TANKERS NOMINATION			
GENERAL			
Taker's Name:		Nominator Company:	
IMO Number:			
Flag:	Owner:	Charterer:	Main Agents: Local Agent:
Crude Oil:	IMO Number:	IMO Number:	Load <input type="text"/> Discharge <input type="text"/> BBLS at 60 °F M ³ at 15°C
TANKER'S INFORMATION PROPORTIONED BY THE NOMINATOR			
ITEM	NOMINATOR INFORMATION		TERMINAL REQUIREMENT
Built (year)			Maximum 25 years old For ships => 20 years, to send a copy of the C.A.P. Certificate. Only Vessels with Ratings 1 or 2 will be accepted.
Original DWT at maximum summer draft (For Multiple DWT vessels, see Annex)	Tons.		Pta Cigüeña Max= 106.000 t Pta Ancla Max= 70.000 t Backup Buoy Max= 70.000 t All Buoys Min= 30.000 t
<i>Indicate whether you will complete de anex or not: YES / NO</i>			
Maximun summer draft	Mts		13,75 m. (45') max.
Manifold connection flange diameter	Inches		1 x 12" - ASME B16.5 Class = 150
Lifting capacity of manifold crane	SWL= tons.		SWL = 10 t. Minimum
Manifold height above waterline	Full loaded= Mts Ballast= Mts		Max= 18,5 Mts.
Nº of cargo tanks / 98% capacity	Tanks / m³		
BCM	Mts.		Pta. Cigüeña Max= 130 mts Pta. Ancla Max= 120 mts
Maximum discharging pressure at manifold (Only unloading ops.)	Kg/cm²		Max. Both SPM = 7 Kg/cm ²
Bow Stopper (Recommendations OCIMF 2007)			Compulsory / Chaff Chain 76mm.
IGS			Compulsory
OCIMF's VPQ			Compulsory to attach a copy
Local Company that respond in case of pollution	Name:	Tel:	
		e-mail:	
Vetting Inspection - Major Oil Company Ship registered as "ACCEPTABLE"	Name:	Expiration Date:	
	E-mail:	Tel.	

	MARITIME TERMINAL PTO. ROSALES		PRO-OPE-RE-049
			REV. 04
TANKERS NOMINATION			
THE NOMINATOR COMPANY DECLARES THAT:			
1- Nominated Vessel and it's owner are not on Sanction Lists.			
2- The nominated vessel is not under Sanctioned Flag.			
3- The vessel is not carrying product from a Sanctioned Country.			
4- Ports of loading and Discharge not located in Sanctioned Countries.			
TANKER'S LIMITATIONS			
Punta Ancla SPM / Backup SPM: For tankers up to DWT=70.000 t. (maximum summer draft). Minimum accepted DWT=30.000 t. For multiple DWT vessels, see Annex			
Punta Cigüeña SPM: For tankers up to DWT= 106.000 t. (max summer draf). Vessels above DWT= 70.000 t. will keep pilot on board during all the operation independently of the quantity of crude oil to load and/or discharge. The pilot will be contracted and paid by Owner / Charterer / Maritime Agency. Mooring Operations to be carried out only with daylight. The mooring manoeuvre will be carried out only with daylight. Minimum accepted DWT=30.000t. Re-measured and multiple DWT vessels are not accepted.			
NOMINATOR COMPANY RESPONSIBILITY			
Please take notice that the data provided herein by the Nominator Company are considered as an affidavit, assuming this one the responsibility for the veracity of such data.			
If the data provided do not coincide with the real features of the nominated ship, Oiltanking - Ebytem S.A. has the right to reject it and the nominated tanker shall not be authorized to carry out the programmed operation.			
The Nominator Company shall be the only and exclusive responsible for the damages and / or costs that the cancellation of the operation could cause to Oiltanking - Ebytem S.A., and / or the producer and / or Third Parties.			
Likewise the Nominator Company is obliged to keep Oiltanking-Ebytem S.A. undamaged in the event of any claims that the latter could receive.			
NOMINATOR			
COMPANY	SIGNATURE AND NAME	TEL. / e-mail	
OILTANKING-EBYTEM S.A. EVALUATION			
RESULT	REJECT-MOTIVE	DATE	SIGNATURE AND NAME

	MARITIME TERMINAL PTO. ROSALES		PRO-OPE-RE-049
			REV. 04
<p align="center">ANNEX:</p> <p align="center">Nomination of a vessel with Multiple Deadweight</p>			
TANKER'S INFORMATION PROPORTIONED BY THE NOMINATOR			
ITEM	NOMINATOR INFORMATION	TERMINAL REQUIREMENT	
Original DWT at maximum summer draft	Tons.		
New DWT at maximum summer draft	Tons.	To operate at Punta Ancla and Spare buoys Max DWT= 70.000 t.	
Max draft for New DWT	metres		
Loadline Certificate	Attach a copy	Compulsory	
Tonnage Certificate	Attach a copy	Compulsory	
Overall Length of the vessel	metres	Max. 228.0 m.	
Beam	metres	Max. 32.4 m	
Depth	metres	Max. 21.0 m	
NOMINATOR			
COMPANY	SIGNATURE AND NAME	TEL. / e-mail	
OILTANKING-EBYTEM S.A. EVALUATION			
RESULT	REJECT-MOTIVE	DATE	SIGNATURE AND NAME